




**US Army Corps
of Engineers**

Hydrologic Engineering Center

HEC-2 Water Surface Profiles Program



Technical Paper No. 140

August 1992

Approved for Public Release. Distribution Unlimited.

DTIC QUALITY INSPECTED 8

19950511 053

Papers in this series have resulted from technical activities of the Hydrologic Engineering Center. Versions of some of these have been published in technical journals or in conference proceedings. The purpose of this series is to make the information available for use in the Center's training program and for distribution within the Corps of Engineers

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

The contents of this report are not to be used for advertising, publication, or promotional purposes. Citation of trade names does not constitute an official endorsement or approval of the use of such commercial products.

HEC-2 Water Surface Profiles Program

Vernon Bonner¹

Accession For	
NTIS	CRA&I <input checked="" type="checkbox"/>
DTIC	TAB <input type="checkbox"/>
Unannounced <input type="checkbox"/>	
Justification	
By	
Distribution /	
Availability Codes	
Dist	Avail and / or Special
A-1	

Abstract

The Hydrologic Engineering Center (HEC) has been developing generalized computer programs since 1964. The first HEC-2 Water Surface Profiles program was released in 1969. The program was developed by Bill S. Eichert, based on his earlier program Backwater Computations - Any Cross Section. The capabilities of HEC-2, and other HEC programs, have evolved; primarily driven by project and application needs. This incremental program development has continued up to the 1990 release of HEC-2 with Federal Highway culvert capability. While incremental program development will continue at a modest pace, HEC has also embarked on an effort to design and develop the next generation of programs. The current HEC-2 package and the next generation goals are presented.

Basic Capability

The program was developed to compute steady, gradually-varied flow profiles based on the Standard-step procedure (USACE, 1959). The program can compute one to fifteen water surface profiles for either subcritical or supercritical flow regime. Tributary profiles can also be computed, based on computed main-stem water surface elevation. Either SI or Foot-pound data units can be used. The program remains batch processing, with fixed-format input and output files. PC utilities have been developed to provide interactive graphical and tabular output (Bonner, 1990a).

¹Chief, Training Division, Hydrologic Engineering Center, 609 Second Street, Davis, CA 95616.

Presented 4 August 1992 at the ASCE Water Forum '92, Baltimore, MD.

Profile Calculations

Starting water-surface elevation can be based on a given water surface elevation, rating curve, estimated energy slope, or critical depth.

Cross sections are defined in X-Y coordinates, and are separated by three reach lengths for the left and right overbanks, and channel flow paths. A cross section can be repeated, can be vertically adjusted by an incremental elevation change, and horizontally adjusted by a constant ratio. Options can be used to limit the effective flow area in the cross section.

Manning's "n" values can be defined for three flow elements, or "n" can vary by stationing across the section, or vary with depth in the channel. Alternatively, relative roughness coefficients "k" can be defined. Given "k", the program will compute an equivalent "n" value based on the hydraulic radius for the water surface elevation (HEC, 1990a, Eq 14).

Average friction slope is estimated using the Average Conveyance for the two sections in a step. Optionally, Average Friction Slope, Geometric Mean Friction Slope, or Harmonic Mean Friction Slope can be used. The program also has a program-determined averaging option that is based on the "profile type" (HEC, 1990a, p 22). Friction loss is computed using a flow-weighted reach length times the average friction slope. Additionally, form losses are computed based on the change in velocity head, if optional Contraction and Expansion Coefficients are defined.

Composite "n" values are computed for the channel (Chow, 1959, Eq 6-17) when the "n" value in the channel changes horizontally and the equivalent side slope of the channel subsection is steeper the 5H to 1V (Davidian, 1984, p 21). Optional input can change the slope criterion, or over-ride the program feature.

Input requirements were modified to eliminate mandatory three title records for each profile and blank records to end the run. Blank lines can be in the input file and "*" Remark records can be used to annotate the input file.

Output for flow distribution was modified to include average depth in each overbank element, as shown below:

FLOW DISTRIBUTION FOR SECNO= 33700.00									
CWSEL= 702.17									
STA=	57.	130.	240.	245.	285.	410.	457.	522.	
PER Q=	6.5	18.7	1.0	43.6	21.5	6.2	2.6		
AREA=	325.1	766.8	39.9	645.8	878.4	280.6	196.4		
VEL=	1.6	1.9	2.0	5.4	2.0	1.8	1.0		
DEPTH=	4.4	7.0	8.0	16.1	7.0	6.0	3.0		

Output summary tables can be developed with interactive PC program SUMPO and simple cross-section, profile, and rating curve plots can be developed with PC program PLOT2 (Bonner, 1990a).

Bridge & Culverts

When bridge crossings obstruct the overbank flow area, the transition of flow from overbank area to open channel area, and back to overbank flow, is modelled by the definition of cross-section effective flow area. The difference among the HEC-2 bridge and culvert options is in the method used to compute the bridge structure loss.

Normal Bridge provides a conveyance-based treatment of bridge crossings. Cross sections in the bridge are defined by adding bridge geometric data to eliminate the cross-sectional area blocked by the bridge. Conveyance calculations consider the added wetted perimeter and the obstructed area caused by the bridge.

Special Bridge provides hydraulic equations for low, pressure, road overflow, and flow combinations. Low-flow losses are based on impact loss due to bridge piers. Pressure flow uses a form of the orifice equation, and bridge over-flow is modelled with the weir equation. The bridge routine can handle combinations of pressure and weir, or low-flow and weir-flow.

Special Culvert provides the hydraulic equations from the Federal Highway Administration procedures (FHWA, 1985). All combinations of flow, considering both inlet and outlet control, can be computed for circular and box culverts. Multiple identical culverts are analyzed assuming flow is equally distributed among the culverts. The input for the culvert routine mimics that for the Special Bridge.

Federal Highway Bridge Hydraulics "WSPRO" (Sherman, et.al, 1986) have been added to HEC-2 in a test application. The present configuration is literally a "splice," with the input read, bridge loss calculations, and bridge output all performed within WSPRO code. The solution then returns to HEC-2 profile computations with the bridge result.

Program Options

Channel Modification - One to three channel templates can be defined at a cross section. Input options support the computation of a base profile for existing conditions and additional profiles with cross sections modified based on the defined templates. With multiple templates, the modified channel can be a compound cut (e.g., low-flow and flood flow templates) or different template scales and locations can be evaluated in a single multiple profile computer run. Both channel reach length and Manning's "n" value can be changed for the modified channel.

Floodway Routines - Six methods are provided to define a floodway within the floodplain cross sections (Bonner, 1988). Several methods were developed to estimate the floodway limits based on FEMA criteria and a "target" increase in water surface elevation (FEMA, 1985). Special output tables are provided to support the reporting requirements for a FEMA flood insurance study.

Split-flow Routine - Lateral overflows can be modelled using a weir equation, normal depth, or a rating curve. Up to 100 overflow reaches can be defined. The flow lost at each overflow is computed, the channel flow is adjusted, and the computed profile is based on the remaining flow in the channel. All or a proportion of the lost flow can be returned at a downstream location. The routine can be used to model diversions, side-overflow weirs, levee overflow, or flow lost over a drainage divide (Montalvo, 1982).

Ice Option - A layer of floating ice can be defined by ice thickness, "n" value, and specific gravity. The cross-section conveyance calculations consider loss of flow area, added wetted perimeter, and computed composite "n" value. In addition to the hydraulic calculations, the potential for ice jams is determined using Pariset's ice stability function (HEC, 1990a, p 25).

Storage-outflow Data - The program computes the cumulative volume of water, under the water surface profile, in a river reach. Storage-outflow data can be provided, in HEC-1 Flood Hydrograph input format (HEC, 1990b), based on multiple water surface profiles. By computing profiles for a range of discharges, and specifying the cross-sections at the ends of the routing reach(s), storage-routing data can be provided in HEC-1 format, including record identifiers (Bonner, 1990b).

Modified Cross-Section Input File - This option provides an input data file, in basic X-Y coordinates (GR records), that incorporates cross-section changes made within HEC-2 with the application of section modification options. This option is useful when additional modeling, beyond the capabilities of the program options, is required. For example, you can obtain a data set created with the Channel Modification routine to perform analysis of a new bridge crossing or additional reach modifications.

Next Generation HEC-2

While maintenance and minor modifications continue with HEC-2 and other programs, HEC started a new software development project last fiscal year. The NexGen (*Next Generation*) project is a five-year effort, under the Corps' R&D Program, to develop the replacement software operating and utilizing the full capabilities of the Engineering Workstation.

During last fiscal year, preliminary requirements documents were developed for catchment, river, reservoir, and flood-damage analysis. The river analysis system is envisioned to provide one-dimensional computations for steady and unsteady flow, plus sediment transport. These computational capabilities will

operate from a common geometric database for a river reach, or system. This will allow the modeler to move from steady to unsteady flow without having to reformulate the river-reach data. Also, graphics and output tables can be provided to support all 1-D modeling activities. The requirements document also proposed the development of a simple standard-step model as a prototype for the system.

During this fiscal year, the catchment model prototype is under development on a Unix workstation. This effort will address issues concerning graphical user interface, data flow and interaction, and general system architecture. The standard-step model prototype is under development in a DOS Windows environment. Using Windows allows us to design a user interface and develop the computational modules without dealing with multi-processing workstation issues.

While HEC-2 capabilities are the bases for the new model development, some of the basic building blocks are being developed "from scratch". The goal is to have computational modules that can support several purposes and allow user controlled interactive computations, when possible. The existing code for water surface profiles is too entangled with other program options. Once the basic standard-step program is functional, bridges and culverts will be added. Much of the bridge and culvert code will be salvaged from the present HEC-2. The intermediate product may be a Windows-based interactive steady flow model.

Input options will include existing HEC-2 data files, XYZ data from terrain models, and screen-menu entry. Easy graphical displays of input will include graphical editing of geometric data and some input parameters. When appropriate, computations can proceed one section at a time, or multiple profile batch processing like the present model. Graphical and tabular output will be provided.

Closely following the steady-flow model, an unsteady flow capability will be developed using the same basic geometric data. HEC is presently working with UNET, an unsteady-flow network model (Barkau, 1991). The program utilizes HEC-2 input to define the geometric data, making it easier for modelers familiar with HEC-2 to develop an unsteady flow model. Time-series data (hydrographs) are read from a random access datafile, HEC-DSS (HEC, 1990c). HEC-DSS is also used to store model results. Graphical and tabular displays of DSS data are provided with program DISPLAY.

The NexGen is an ambitious project for a small office to undertake. As with most software development, the delivery dates are in the future (*vapor-ware*) and the forecasts tend to be overly optimistic. However, we believe that it is time to build the models for the future. We hope that the combination of maintaining and modestly improving existing software, plus providing intermediate "prototype" programs, will keep the engineering community with sufficient computational capability to meet many of their hydrologic modeling needs.

References

- Barkau, R.L., (1991). "UNET One-Dimensional Unsteady Flow Through a Full Network of Open Channels," Draft User's Manual, Hydrologic Engineering Center, Davis, CA.
- Bonner, V.R. (1988). "Floodway Determination Using Computer Program HEC-2," Training Document No. 5, Hydrologic Engineering Center, Davis, CA.
- Bonner, V.R. (1990a). "Computing Water Surface Profiles with HEC-2 on a Personal Computer," Training Document No. 26, Hydrologic Engineering Center, Davis, CA.
- Bonner, V.R. (1990b). "River Routing with HEC-1 and HEC-2," Training Document No. 30, Hydrologic Engineering Center, Davis, CA.
- Chow, V.T. (1959). Open Channel Hydraulics. McGraw-Hill, New York, NY.
- Davidian, J. (1984). "Computation of Water-Surface Profiles in Open Channels," Techniques of Water-Resources Investigations, United States Geological Survey, Book 3, Chapter A15, Washington, DC.
- FEMA, (1985). "Flood Insurance Study Guidelines and Specifications for Study Contractors," Federal Emergency Management Agency, Washington, DC.
- FHWA, (1985). "Hydraulic Design of Highway Culverts," Hydraulic Design Series No. 5, US Department of Transportation, Washington, DC.
- HEC, (1990a). "HEC-2 Water Surface Profiles," User's Manual, Hydrologic Engineering Center, Davis, CA.
- HEC, (1990b). "HEC-1 Flood Hydrograph Package," User's Manual, Hydrologic Engineering Center, Davis, CA.
- HEC, (1990c). "HEC-DSS User's Guide and Utility Program Manuals," Hydrologic Engineering Center, Davis, CA.
- Montalvo, A.E. (1982). "Application of the HEC-2 Split Flow Option," Training Document No. 5, Hydrologic Engineering Center, Davis, CA.
- Shearman, J.O., Kirby, W.H., Schneider, V.R., and Flippo, H.N., (1986). "Bridge Waterways Analysis Model," Research Report No. FHWA/RD-86/108, U.S. Geological Survey, WRD, Reston, VA.
- USACE, (1959). "Backwater Curves in River Channels," US Army Corps of Engineers, EM 1110-2-1409, Washington, DC.

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
1a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED			1b. RESTRICTIVE MARKINGS		
2a. SECURITY CLASSIFICATION AUTHORITY			3. DISTRIBUTION/AVAILABILITY OF REPORT		
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE					
4. PERFORMING ORGANIZATION REPORT NUMBER(S) TECHNICAL PAPER NO. 140 (TP-140)			5. MONITORING ORGANIZATION REPORT NUMBER(S)		
6a. NAME OF PERFORMING ORGANIZATION HYDROLOGIC ENGINEERING CENTER		6b. OFFICE SYMBOL (If applicable) CEWRC-HEC	7a. NAME OF MONITORING ORGANIZATION WATER RESOURCES SUPPORT CENTER		
6c. ADDRESS (City, State, and ZIP Code) 609 SECOND STREET DAVIS, CA 95616			7b. ADDRESS (City, State, and ZIP Code) 7701 TELEGRAPH ROAD ALEXANDRIA, VA 22310-3868		
8a. NAME OF FUNDING/SPONSORING ORGANIZATION		8b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER		
8c. ADDRESS (City, State, and ZIP Code)			10. SOURCE OF FUNDING NUMBERS		
			PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.
			WORK UNIT ACCESSION NO.		
11. TITLE (Include Security Classification) HEC-2 WATER SURFACE PROFILES PROGRAM					
12. PERSONAL AUTHOR(S) Vernon R. Bonner					
13a. TYPE OF REPORT Technical Paper		13b. TIME COVERED FROM _____ TO _____		14. DATE OF REPORT (Year, Month, Day) AUGUST 1992	
15. PAGE COUNT 12					
16. SUPPLEMENTARY NOTATION Presented at the ASCE Water Forum '92, 2-6 August 1992, Baltimore, MD.					
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)		
FIELD	GROUP	SUB-GROUP	Water surface profiles, HEC-2 computer program, microcomputer		
19. ABSTRACT (Continue on reverse if necessary and identify by block number) The first HEC-2 Water Surface Profiles program was released in 1969. The capabilities of HEC-2, and other HEC programs, have evolved; primarily driven by project and application needs. This incremental program development has continued up to the 1990 release of HEC-2 with Federal Highway culvert capability. While incremental program development will continue at a modest pace, HEC has also embarked on an effort to design and develop the next generation of programs. The current HEC-2 package and the next generation goals are presented.					
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT <input checked="" type="checkbox"/> UNCLASSIFIED/UNLIMITED <input type="checkbox"/> SAME AS RPT. <input type="checkbox"/> DTIC USERS			21. ABSTRACT SECURITY CLASSIFICATION		
22a. NAME OF RESPONSIBLE INDIVIDUAL VERNON R. BONNER, Chief, Training Division			22b. TELEPHONE (Include Area Code) (916) 756-1104		22c. OFFICE SYMBOL CEWRC-HEC-T

TECHNICAL PAPER SERIES

- | | | | |
|-------|--|-------|---|
| TP-1 | Use of Interrelated Records to Simulate Streamflow | TP-38 | Water Quality Evaluation of Aquatic Systems |
| TP-2 | Optimization Techniques for Hydrologic Engineering | TP-39 | A Method for Analyzing Effects of Dam Failures in Design Studies |
| TP-3 | Methods of Determination of Safe Yield and Compensation Water from Storage Reservoirs | TP-40 | Storm Drainage and Urban Region Flood Control Planning |
| TP-4 | Functional Evaluation of a Water Resources System | TP-41 | HEC-5C, A Simulation Model for System Formulation and Evaluation |
| TP-5 | Streamflow Synthesis for Ungaged Rivers | TP-42 | Optimal Sizing of Urban Flood Control Systems |
| TP-6 | Simulation of Daily Streamflow | TP-43 | Hydrologic and Economic Simulation of Flood Control Aspects of Water Resources Systems |
| TP-7 | Pilot Study for Storage Requirements for Low Flow Augmentation | TP-44 | Sizing Flood Control Reservoir Systems by Systems Analysis |
| TP-8 | Worth of Streamflow Data for Project Design - A Pilot Study | TP-45 | Techniques for Real-Time Operation of Flood Control Reservoirs in the Merrimack River Basin |
| TP-9 | Economic Evaluation of Reservoir System Accomplishments | TP-46 | Spatial Data Analysis of Nonstructural Measures |
| TP-10 | Hydrologic Simulation in Water-Yield Analysis | TP-47 | Comprehensive Flood Plain Studies Using Spatial Data Management Techniques |
| TP-11 | Survey of Programs for Water Surface Profiles | TP-48 | Direct Runoff Hydrograph Parameters Versus Urbanization |
| TP-12 | Hypothetical Flood Computation for a Stream System | TP-49 | Experience of HEC in Disseminating Information on Hydrological Models |
| TP-13 | Maximum Utilization of Scarce Data in Hydrologic Design | TP-50 | Effects of Dam Removal: An Approach to Sedimentation |
| TP-14 | Techniques for Evaluating Long-Term Reservoir Yields | TP-51 | Design of Flood Control Improvements by Systems Analysis: A Case Study |
| TP-15 | Hydrostatistics - Principles of Application | TP-52 | Potential Use of Digital Computer Ground Water Models |
| TP-16 | A Hydrologic Water Resource System Modeling Techniques | TP-53 | Development of Generalized Free Surface Flow Models Using Finite Element Techniques |
| TP-17 | Hydrologic Engineering Techniques for Regional Water Resources Planning | TP-54 | Adjustment of Peak Discharge Rates for Urbanization |
| TP-18 | Estimating Monthly Streamflows Within a Region | TP-55 | The Development and Servicing of Spatial Data Management Techniques in the Corps of Engineers |
| TP-19 | Suspended Sediment Discharge in Streams | TP-56 | Experiences of the Hydrologic Engineering Center in Maintaining Widely Used Hydrologic and Water Resource Computer Models |
| TP-20 | Computer Determination of Flow Through Bridges | TP-57 | Flood Damage Assessments Using Spatial Data Management Techniques |
| TP-21 | An Approach to Reservoir Temperature Analysis | TP-58 | A Model for Evaluating Runoff-Quality in Metropolitan Master Planning |
| TP-22 | A Finite Difference Method for Analyzing Liquid Flow in Variably Saturated Porous Media | TP-59 | Testing of Several Runoff Models on an Urban Watershed |
| TP-23 | Uses of Simulation in River Basin Planning | TP-60 | Operational Simulation of a Reservoir System with Pumped Storage |
| TP-24 | Hydroelectric Power Analysis in Reservoir Systems | TP-61 | Technical Factors in Small Hydropower Planning |
| TP-25 | Status of Water Resource Systems Analysis | TP-62 | Flood Hydrograph and Peak Flow Frequency Analysis |
| TP-26 | System Relationships for Panama Canal Water Supply | TP-63 | HEC Contribution to Reservoir System Operation |
| TP-27 | System Analysis of the Panama Canal Water Supply | TP-64 | Determining Peak-Discharge Frequencies in an Urbanizing Watershed: A Case Study |
| TP-28 | Digital Simulation of an Existing Water Resources System | TP-65 | Feasibility Analysis in Small Hydropower Planning |
| TP-29 | Computer Applications in Continuing Education | TP-66 | Reservoir Storage Determination by Computer Simulation of Flood Control and Conservation Systems |
| TP-30 | Drought Severity and Water Supply Dependability | TP-67 | Hydrologic Land Use Classification Using LANDSAT |
| TP-31 | Development of System Operation Rules for an Existing System by Simulation | TP-68 | Interactive Nonstructural Flood-Control Planning |
| TP-32 | Alternative Approaches to Water Resource System Simulation | TP-69 | Critical Water Surface by Minimum Specific Energy Using the Parabolic Method |
| TP-33 | System Simulation for Integrated Use of Hydroelectric and Thermal Power Generation | TP-70 | Corps of Engineers Experience with Automatic Calibration of a Precipitation-Runoff Model |
| TP-34 | Optimizing Flood Control Allocation for a Multipurpose Reservoir | TP-71 | Determination of Land Use from Satellite Imagery for Input to Hydrologic Models |
| TP-35 | Computer Models for Rainfall-Runoff and River Hydraulic Analysis | TP-72 | Application of the Finite Element Method to Vertically Stratified Hydrodynamic Flow and Water Quality |
| TP-36 | Evaluation of Drought Effects at Lake Atitlan | | |
| TP-37 | Downstream Effects of the Levee Overtopping at Wilkes-Barre, PA, During Tropical Storm Agnes | | |

- TP-73 Flood Mitigation Planning Using HEC-SAM
- TP-74 Hydrographs by Single Linear Reservoir Model
- TP-75 HEC Activities in Reservoir Analysis
- TP-76 Institutional Support of Water Resource Models
- TP-77 Investigation of Soil Conservation Service Urban Hydrology Techniques
- TP-78 Potential for Increasing the Output of Existing Hydroelectric Plants
- TP-79 Potential Energy and Capacity Gains from Flood Control Storage Reallocation at Existing U. S. Hydropower Reservoirs
- TP-80 Use of Non-Sequential Techniques in the Analysis of Power Potential at Storage Projects
- TP-81 Data Management Systems for Water Resources Planning
- TP-82 The New HEC-1 Flood Hydrograph Package
- TP-83 River and Reservoir Systems Water Quality Modeling Capability
- TP-84 Generalized Real-Time Flood Control System Model
- TP-85 Operation Policy Analysis: Sam Rayburn Reservoir
- TP-86 Training the Practitioner: The Hydrologic Engineering Center Program
- TP-87 Documentation Needs for Water Resources Models
- TP-88 Reservoir System Regulation for Water Quality Control
- TP-89 A Software System to Aid in Making Real-Time Water Control Decisions
- TP-90 Calibration, Verification and Application of a Two-Dimensional Flow Model
- TP-91 HEC Software Development and Support
- TP-92 Hydrologic Engineering Center Planning Models
- TP-93 Flood Routing Through a Flat, Complex Flood Plain Using a One-Dimensional Unsteady Flow Computer Program
- TP-94 Dredged-Material Disposal Management Model
- TP-95 Infiltration and Soil Moisture Redistribution in HEC-1
- TP-96 The Hydrologic Engineering Center Experience in Nonstructural Planning
- TP-97 Prediction of the Effects of a Flood Control Project on a Meandering Stream
- TP-98 Evolution in Computer Programs Causes Evolution in Training Needs: The Hydrologic Engineering Center Experience
- TP-99 Reservoir System Analysis for Water Quality
- TP-100 Probable Maximum Flood Estimation - Eastern United States
- TP-101 Use of Computer Program HEC-5 for Water Supply Analysis
- TP-102 Role of Calibration in the Application of HEC-6
- TP-103 Engineering and Economic Considerations in Formulating
- TP-104 Modeling Water Resources Systems for Water Quality
- TP-105 Use of a Two-Dimensional Flow Model to Quantify Aquatic Habitat
- TP-106 Flood-Runoff Forecasting with HEC-1F
- TP-107 Dredged-Material Disposal System Capacity Expansion
- TP-108 Role of Small Computers in Two-Dimensional Flow Modeling
- TP-109 One-Dimensional Model For Mud Flows
- TP-110 Subdivision Froude Number
- TP-111 HEC-5Q: System Water Quality Modeling
- TP-112 New Developments in HEC Programs for Flood Control
- TP-113 Modeling and Managing Water Resource Systems for Water Quality
- TP-114 Accuracy of Computed Water Surface Profiles - Executive Summary
- TP-115 Application of Spatial-Data Management Techniques in Corps Planning
- TP-116 The HEC's Activities in Watershed Modeling
- TP-117 HEC-1 and HEC-2 Applications on the MicroComputer
- TP-118 Real-Time Snow Simulation Model for the Monongahela River Basin
- TP-119 Multi-Purpose, Multi-Reservoir Simulation on a PC
- TP-120 Technology Transfer of Corps' Hydrologic Models
- TP-121 Development, Calibration and Application of Runoff Forecasting Models for the Allegheny River Basin
- TP-122 The Estimation of Rainfall for Flood Forecasting Using Radar and Rain Gage Data
- TP-123 Developing and Managing a Comprehensive Reservoir Analysis Model
- TP-124 Review of the U.S. Army Corps of Engineering Involvement With Alluvial Fan Flooding Problems
- TP-125 An Integrated Software Package for Flood Damage Analysis
- TP-126 The Value and Depreciation of Existing Facilities: The Case of Reservoirs
- TP-127 Floodplain-Management Plan Enumeration
- TP-128 Two-Dimensional Floodplain Modeling
- TP-129 Status and New Capabilities of Computer Program HEC-6: "Scour and Deposition in Rivers and Reservoirs"
- TP-130 Estimating Sediment Delivery and Yield on Alluvial Fans
- TP-131 Hydrologic Aspects of Flood Warning - Preparedness Programs
- TP-132 Twenty-five Years of Developing, Distributing, and Supporting Hydrologic Engineering Computer Programs
- TP-133 Predicting Deposition Patterns in Small Basins
- TP-134 Annual Extreme Lake Elevations by Total Probability Theorem
- TP-135 A Muskingum-Cunge Channel Flow Routing Method for Drainage Networks
- TP-136 Prescriptive Reservoir System Analysis Model - Missouri River System Application
- TP-137 A Generalized Simulation Model for Reservoir System Analysis
- TP-138 The HEC NexGen Software Development Project
- TP-139 Issues for Applications Developers
- TP-140 HEC-2 Water Surface Profiles Program
- TP-141
- TP-142 Systems Analysis Applications at the Hydrologic Engineering Center
- TP-143 Runoff Prediction Uncertainty for Ungauged Agricultural Watersheds
- TP-144 Review of GIS Applications in Hydrologic Modeling
- TP-145 Application of Rainfall-Runoff Simulation for Flood Forecasting
- TP-146 Application of the HEC Prescriptive Reservoir Model in the Columbia River System